



- NOTE:
1. TO ENSURE PROPER SUBSURFACE DRAINAGE, THE SUBGRADE WILL BE CONSTRUCTED WITH 1% PITCH TOWARD INSTALLED DRAINAGE PIPE.
 2. FINISH MINIMUM WIDTH SHALL BE 33" AFTER MIX HAS BEEN APPLIED.
 3. TEE SURFACE SHALL HAVE A 17' MIN. RADIUS TO ACCOMMODATE MAINTENANCE EQUIPMENT.

HANCOR, INC. HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO HANCOR. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. HANCOR HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS HANCOR INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION, IT IS THE DESIGN ENGINEERS RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

REV.	DESCRIPTION	BY	DATE	CHKD
1	UPDATE DRAWING	TJR	9/24/07	

TEE PROFILE WITH CORRUGATED PIPE DETAIL

DRAWING NUMBER: STD-1207



DATE	12/20/99
SCALE	NTS
SHEET	OF