



- NOTE:**
1. TRENCH MUST BE NO LESS THAN 6" WIDE & 8" DEEP.
 2. USE TRENCH BACKFILL COMPATIBLE WITH SAND IN BUNKER TO CREATE BRIDGING FACTOR.
 3. BUNKER DIMENSIONS AND CONFIGURATIONS VARY. BUNKERS SUBJECT TO FIELD VERIFICATIONS AND ADJUSTMENT BY GOLF COURSE ARCHITECT.

© 2007 HANCOR, INC.

HANCOR, INC. HAS PREPARED THIS DETAIL BASED ON INFORMATION PROVIDED TO HANCOR. THIS DRAWING IS INTENDED TO DEPICT THE COMPONENTS AS REQUESTED. HANCOR HAS NOT PERFORMED ANY ENGINEERING OR DESIGN SERVICES FOR THIS PROJECT, NOR HAS HANCOR INDEPENDENTLY VERIFIED THE INFORMATION SUPPLIED. THE INSTALLATION DETAILS PROVIDED HEREIN ARE GENERAL RECOMMENDATIONS AND ARE NOT SPECIFIC FOR THIS PROJECT. THE DESIGN ENGINEER SHALL REVIEW THESE DETAILS PRIOR TO CONSTRUCTION. IT IS THE DESIGN ENGINEER'S RESPONSIBILITY TO ENSURE THE DETAILS PROVIDED HEREIN MEETS OR EXCEEDS THE APPLICABLE NATIONAL, STATE, OR LOCAL REQUIREMENTS AND TO ENSURE THAT THE DETAILS PROVIDED HEREIN ARE ACCEPTABLE FOR THIS PROJECT.

REV.	DESCRIPTION	TJR	09/24/07	CKS
1	UPDATED DRAWING			

BUNKER DRAINAGE PROFILE (SAND TRAP) W/ CORRUGATED PIPE

DRAWING NUMBER: STD-1209

401 OLIVE ST.
FINDLAY, OHIO 45839

DATE: 12-20-99
SCALE: NTS
SHEET: OF